

Specifications

Analog Input/Output	Balanced (XLR), Unbalanced (RCA Pin)
Digital Input/Output	AES/EBU (XLR), coaxial (RCA Pin)
Number of channels	2
Tape format	Digital Audio Tape
D/A resolution	Standard: 16 bit, Long Play: 12 bit
Recording time	Standard: 120 Min, Long Play: 240 Min (w/ 120 min tape)
Sample rates	48kHz, 44.1kHz, 32kHz
Frequency response	20-20kHz(+/- .5dB), Long Play: 20-14.5kHz (+/- .5dB)
S/N Ratio	>90dB
THD	<0.05%
Wow & Flutter	Below measurable limits
Phones	Stereo phone jack
Remote Interface	Parallel DIN 8p-pin
Weight	Approx 7.2kg
Dimensions	482(W) X 145(H) X 335(D) mm
Supplied accessories	wireless remote commander, AC power

HIGHLIGHTS

- High-reliability 4 D.D transport
- Extremely easy to use with Jog Shuttle Wheel
- Flexible setup menu
- Remote controllable
- Wide range of audio interface options
- Super Bit Mapping In the AD circuitry
- R-Core Transformer for reduced leakage flux
- Independent Channel 1/Channel 2 recording level volume controls to eliminate cross talk